XKEYSCORE Workflows

19 September 2011

What is a workflow?

- **Workflows automate queries.**
  - One-time
  - Standing
- **Every search type can be a workflow.**
  - Same functionality and capability
- **Follow on actions**
  - Email alert
  - Download actions
  - Metadata summary

Who can submit a workflow?

- # Anyone!

- # One owner per workflow, but using follow-on actions:

  - Multiple-users can be notified of results and/or sent summary information

  - Result table can be automatically shared

- # If ownership needs to be changed, a ticket can be submitted to the team.

What can I do with a workflow?

- ## Workflows can be configured to run once
- ## Workflows can be configured to run daily
  - ### Every 1, 2, 3, 4, 6, 8, 12 or 24 hours
  - ### You can set an offset to start running at a certain hour
- ## Download results
- ## Email results and email alerts
- ## MAILORDER results
- ## MySQL report

Why do I want a workflow?

- **XKEYSCORE has a rolling buffer of data**
- **Repetitive queries**
- **Sigdev purpose**
  - Fingerprint and appid testing
- **Queries take a long time during high times**
- **Follow on actions**
  - Google Earth data
  - Statistics
  - Customizable – write a script!

How do I setup a workflow?

- Two main ways
  - Based on the results of a recent query
    - Simplifies the process & more likely to produce the desired result!
    - This is done by right-clicking on the result set from the desired query and selecting *Create Workflow from this Search*. This populates the Workflow Wizard with the same criteria that was used by the selected query.

  - From scratch using the Workflow Wizard
    - Not recommended – but we'll show you anyway

How do I setup a workflow?

- The next ten slides demonstrate how to step through the workflow wizard from scratch

- But if you create the workflow from an existing query result many of the steps will already be correctly populated!

Right click to get the menu and choose this option

Result Grid Row Actions

- View Metadata
- View Metadata (New Window)
- Delete Row
- Rename Query
- Share Results..
- Repopulate this Search into Form
- Create Workflow from this Search
- Split Both Sides of Traffic
- Archive Results

Result Grid Cell Actions

- Filter: Query Name Equal 'byz rapt rdp india b...'
- Filter: Query Name Not Equal to 'byz rapt rdp india b...'
- Show Full Cell Value

My Recent Results

Help   Actions ▾   View ▾

	Query Name		Num Results	Num DBs	Datetime Submitted ▾	Query ID
☐	byz rapt rdp india both dir		3006	51 of 51	2011-09-19 17:01:44	jb_e00b
☐	byz rapt rdp class c		132	49 of 51	2011-09-19 16:38:07	jb_e00b9
☐	byz rapt rdp		98	49 of 51	2011-09-19 16:35:36	jb_e00b9
☐	ww bb pin imsi no five eyes (WORKFLOW)	er	9055	54 of 57	2011-09-19 08:55:57	xml_job_2
☐	afghan pin imsi correlation (WORKFLOW)	er	7124	12 of 12	2011-09-18 23:55:19	xml_job_2

How do I setup a workflow?

KEYSCORE

How do I setup a workflow?

First, s... ...a workflo...

Workflow Central Request Wizard

Please select a Search Type.

Full Log

Every session collected, indexed by "standard" DNI meta-data (to/from IP, port, casenotation, application id, sigad, etc).

Search Type Help

Cancel   ◀ Prev   ▶ Next   Submit

How do I setup a workflow?

KEYSCORE

ring or one-

ust be unique per user
must have a justification
justifications

Workflow Central Request Wizard   ×

Basic Information

Query Name:	Find_my_appid
Query Justification:	Testing appid signature
Additional Justification:	▼
Miranda Number:	

Datetime: [1 Day ▼] Start: [2009-03-04 ▣] [00:00 ▲▼] Stop: [2009-03-05 ▣] [23:59 ▲▼] ❷

[Reccurring Search] [**One Time Search**▶]

Basic Features Help   ▼

Runs once over
a set datetime
range

Cancel ◀ Prev   ▶ Next Submit

How do I setup a workflow?

KEYSCORE

Selec _____ ant to

searc

Select a
field to
search

Workflow Central Request Wizard ☒

Add Search Fields

Search Values are **ANDed** by default.

To **OR** Search **Fields:**
* Use the Multiple Field Search tab (below the input fields).
* Select all the fields you wish to search.

To **OR** Search **Values:**
* Type 'OR' between each value (no quotes).

See Search Value Help below for more details or
for a description of boolean logic go to here.

Search Field	Search Value	Remove
From IP Address OR To IP Address	1.2.3.4	✖

Attribute Info	
From IP Address	
To IP Address	
From Port	
To Port	

Single Field Search | **Multiple Field Search**

Search Value Help ▾

or every field,
)u must select
ie PLUS key

Cancel ◀ Prev   ▶ Next   Submit

Group by option

Group b[...] [...]ta results.

- Red[...]
- Retu[...]

Workflow Central Request Wizard

Group Search Fields

Would you like to group any fields?
- ○ No
- ◉ Yes

Group By Type

Table Unique Values: ◉
Global Unique Values: ○

❓ Group By Type Help

Columns to Group By

- Datetime: ☐
- Client IP (X-Fowarded-For): ☐
- Username: ☐
- Attribute Info: ☐
- From IP Address: ☐
- To IP Address: ☐
- From Port: ☐
- To Port: ☐
- From Country (IP): ☐
- To Country (IP): ☐
- From City (IP): ☐
- To City (IP): ☐
- From Latitude (IP): ☐

This option groups each result/table/LATE and concatenated. (overlapping text)

Select the fields you want to group by.

Cancel ◄ Prev ► Next Submit

Select databases

- Choose the search databases you would like to use

  - Can use an alias for multiple databases

  - Prepopulated if created from an existing search

Workflow Central Edit Request Wizard

☐ TAO STAT Team (tao-stat:xs_web_db)

☐ TEC (tc1xks1.tec.ces.nsa:xs_web_db)

☐ TEC DEEPDIVE (xksdd1.tec.ces.nsa:xs_web_db)

☐ TEC SSO DEEPDIVE NOFORN (ssoxksdd1:xs_web_db)

☐ TEC TURTLERACE (turtlerace:xs_web_db)

☐ Timberline SV (timberline-sv:xs_web_db)

☐ TURBULENCE at the TEC (turbotec:xs_web_db)

☐ TURBULENCE MHS live (TURBOPOUND) (turbopound:xs_web_db) **Please only enable if necessary**

☐ TURTLEALE MHS live system (turboale:xs_web_db)

☐ XKSVOIP1 NOFORN (xksvoip-nf:q0)

☐ XKSVOIP2 REL (xksvoip-rel:q0)

☐ Yakima Deep Dive (jacknife-dd:xs_web_db)

☐ Yakima mission system (jacknife:xs_web_db)

☑ Content must exist

Basic Features Help

Cancel ◀ Previous ▶ Next Submit

> If this is selected, results are only returned if the content still exists at site.

Follow on Actions

- Allows you alter your results

- Allows y   content) to another
location.

- Allows y

- Allows y

Workflow Central Edit Request Wizard

Follow-on Actions

Would you like to add any follow on actions

- ○ No
- ● Yes

Script	Script Arguments		Add
Email Alert ▾	Email To:	[ ]	➕
Email Alert	ROWR:	☐ Return Only With Results	
SQL Report	Share Results:	☐ Share Results with users above	
Download Sessions			
Find and Foward VoIP			

An email is sent out once your workflow is completed.

Setup a MySQL statement to alter your results

Download your results to another location.

Used to forward VoIP to NUCLEON

Cancel ◀ Previous   ▶ Next Submit

Email alert

KEYSCORE

Workflow Central Edit Request Wizard ⊠

Follow-on Actions

Would you like to add any follow on actions

○ No

◉ Yes

Script	Script Arguments		Add
Email Alert ▾	Email To:		➕
Email Alert	ROWR:	☐ Return Only With Results	
SQL Report	Share Results:	☐ Share Results with users above	
Download Sessions			
Find and Foward Voip			

Comma delimited email addresses.

This option only sends an email if you workflow has results.

This will make the results appear for all of the listed users

Cancel ◀ Previous   ▶ Next Submit

SQL report

Workflow Central Request Wizard ☒

Follow-on Actions

Would you like to add any follow on actions

○ No
◉ Yes

Script	Script Arguments	Add
SQL Report ▾	Type: [_____] ▾	➕
	Email To: [_____]	
	Email Subject: [_____]	
	Email Content: [_____]	
	Email Attachment: ☐ Email Attachment	
	ROWR: ☐ Return Only With Results	
	Filename: [_____]	
	Mail Order Trigraph: [_____]	
	SQL: SELECT FROM %{OUTPUT_TABLE} WHERE GROUP BY	
	GZIP: ☐ Compress Contents	

Cancel ◀ Prev   ▶ Next Submit

CSV or HTML

Email metadata that a user can set.

This must be a VALID SQL statement.

Example:

SELECT casenotation, sigad

FROM %{OUTPUT_TABLE}

WHERE sigad!=''

GROUP BY casenotation

Download Results

Workflow Central Request Wizard ✕

Follow-on Actions

Would you like to add any follow on actions

○ No
◉ Yes

Script	Script Arguments		Add
Download Sessions ▾	User ID:	[ ]	➕
	Email To:	[ ]	
	Email Subject:	[ ]	
	Email Content:	[ ]	
	ROWR:	☐ Return Only With Results	
	Filename:	[ ]	
	Mail Order Trigraph:	[ ]	
	GZIP:	☐ Compress Contents	
	Send To Agility:	☐ Send To Agility	

Cancel   ◀ Prev   ▶ Next   Submit

You're almost done!

Workflow Central Request Wizard

Workflow Review

This query (Find_my_appid) will search the **Full Log** table in database(s):
  xks-jychan:q0

The query will run **CONTINUOUSLY** executing every **6 hours** beginning at **5:00 EST**

The query will execute the following search criteria:

```
<and>
    <field>From IP Address</field>
    <value>1.2.3.4</value>
</and>

<and>
    <field>To Port</field>
    <value>80</value>
</and>

<and>
    <field>AppID (+Fingerprints)*</field>
    <value>search/google*</value>
</and>
```

Workflow Values | Workflow XML

Cancel ◀ Prev ▶ Next Submit

Workflow Pending

Workflow Approved

KEYSCORE

XKEYSCORE   Welcome: jychan   switch users

Home   Workflow Central   Search   Results   Statistics   Tagging   Preferences   Help

Navigation Menu

- Explorer
  - Home
  - Workflow Central
   - Request
    - My Workflows
  - Search
    - Classic
      - MultiSearch
      - Classic A-M
      - Classic N-Z
    - Common
      - Category DNI
      - Document Metadata
      - Email Addresses
      - Extracted Files
      - Full Log DNI
      - HTTP Activity
      - Phone Number Extractor
      - User Activity
    - Dictionary Hits
    - File Transfer
    - MultiSearch
      - IP Addresses
      - Mac Address
      - Username
    - Network Management
    - Search Wizard
    - User Activity
    - VoIP
    - Wireless
  - Results
    - My Recent Results
    - My Previous Results
    - My Ongoing Results
    - My Downloads
  - Statistics
    - Link Summarization
  - Tagging
    - Local Tagging
    - Tech Extractor Tagging

My Workflows

Help Actions

Query Type

full_log

Workflow: Find_my_appid

```xml
<?xml version="1.0" encoding="UTF-8"?>
<query_jobs>
    <internal_gui>1</internal_gui>
    <datetime_created>1236264295</datetime_created>
    <job>
        <xks_userid>████</xks_userid>
        <xks_user_name>████</xks_user_name>
        <xks_password>18837b706121a0ca</xks_password>
        <search_type>full_log</search_type>
        <query_name>Find_my_appid</query_name>
        <query_justification>Testing appid signature   </query_justification>
        <datetime>
            <interval>6</interval>
            <offset>5</offset>
        </datetime>
        <sql>
            <where>
                <and>
                    <field>fm_ip</field>
                    <value>1.2.3.4</value>
                </and>
                <and>
                    <field>to_ap</field>
                    <value>80</value>
                </and>
                <and>
                    <field>fingerprint</field>
                    <value>search/google*</value>
                </and>
            </where>
            <group_by>to_ip</group_by>
            <indexes>unique key(to_ip)</indexes>
        </sql>
        <advanced>
            <content_must_exist>true</content_must_exist>
            <routing>
                <database>xks-jychan:q0</database>
            </routing>
```

Cancel   Save/Submit

Page 1 of 1   Page Size: 30

Displaying 1 - 1 of 1

Common mistakes

- From IP and To IP with the same value.

- In this view, terms are ANDed together.

- Use Multiple Field Search Tab.

Workflow Central Request Wizard ☒

Add Search Fields

Search Values are **ANDed** by default.
To **OR** Search **Fields:**
  * Use the Multiple Field Search tab (below the input fields).
  * Select all the fields you wish to search.
To **OR** Search **Values:**
  * Type 'OR' between each value (no quotes).

See Search Value Help below for more details or for a description of boolean logic go to here.

Search Field	Search Value	Remove
From IP Address OR To IP Address	1.2.3.4	✖

Attribute Info
From IP Address
To IP Address
From Port
To Port

Single Field Search | **Multiple Field Search**

Search Value Help ▾

Cancel ◀ Prev   ▶ Next Submit

Common mistakes

- Using the multiple field search does not break this up into 3 search<->value pairs.

- Enter each term separately in the singe fieldsearch.

Workflow Central Request Wizard ✕

Add Search Fields

Search Values are **ANDed** by default.
To **OR** Search **Fields**:
  * Use the Multiple Field Search tab (below the input fields).
  * Select all the fields you wish to search.
To **OR** Search **Values**:
  * Type 'OR' between each value (no quotes).

See Search Value Help below for more details or
for a description of boolean logic go to here.

Search Field	Search Value	Remove
From IP Address	1.2.3.4	✖
To IP Address	5.6.7.8	✖
From Port	80	✖

| Single Field Search | Multiple Field Search |

Search Value Help

Cancel ◀ Prev   ▶ Next Submit

Common mistakes

- This will return ALL casenotations.

  - a will be deafeted by "!a" but a does equal "!b"

- All the defeated values must be ANDed together.

Workflow Central Request Wizard ✕

Add Search Fields

Search Values are **ANDed** by default.
To **OR** Search **Fields:**
  * Use the Multiple Field Search tab (below the input fields).
  * Select all the fields you wish to search.
To **OR** Search **Values:**
  * Type 'OR' between each value (no quotes).

See Search Value Help below for more details or
for a description of boolean logic go to here.

Search Field	Search Value	Remove
Casenotation	!a	✖
Casenotation	!b	✖
Casenotation	!c	✖
Casenotation	!d	✖
▼	▼	➕

Single Field Search | Multiple Field Search

Search Value Help ▼

Cancel ◄ Prev   ► Next Submit

Common mistakes

Workflow Central Request Wizard   ☒

Add Search Fields

Search Values are **ANDed** by default.

To **OR** Search **Fields:**
  * Use the Multiple Field Search tab (below the input fields).
  * Select all the fields you wish to search.
To **OR** Search **Values:**
  * Type 'OR' between each value (no quotes).

See Search Value Help below for more details or
for a description of boolean logic go to here.

Search Field	Search Value	Remove
Casenotation	!c	✖
Casenotation	!d	✖
SIGAD	AUC-993	✖
▾	▾	✚

Select the Database(s) to query

☑ ▪AUS sites
☑ ▪F6 sites
☑ ▪NZ sites

☐ **Content must exist**

☑ Check All
☐ Uncheck All

Basic Features Help   ▾

Cance

▪If you are selecting specific SIGADs, only select the sites that have data from that SIGAD.

▪Queries will return faster.

Single SIGAD
sites selected

▪Less work for the system.

Common mistakes

- If you select the SQL Report option, make sure you put a valid SQL statement!

SQL statement filled in:

SELECT casenotation, count(*) EMPTY statement FROM %{OUTPUT_TABLE}

WHERE casenotation!="

GROUP BY casenotation

Workflow Central Request Wizard   ✕

Follow-on Actions

Would you like to add any follow on actions

○ No
● Yes

Script	Script Arguments	Add
SQL Report ▾		➕

Type: CSV ▾

Email To: analyst@work.com

Email Subject: My Workflow Results

Email Content: Bad SQL - empty

Email Attachment: ☐ Email Attachment

ROWR: ☐ Return Only With Results

Filename:

Mail Order Trigraph:

SQL:
```
SELECT casenotation, count(*)
FROM %{OUTPUT_TABLE}
WHERE casenotation!="
GROUP BY casenotation
```

GZIP: ☐ Compress Contents

Cancel ◀ Prev   ▶ Next   Submit

Questions?
xks_workflow@r1.r.nsa